



SUPER STAR X-TREME

MODEL	43-000 Super Star X-treme (gas) 3-WD
POWER	18hp (13.5 kW) Vanguard V twin cylinder , air cooled, gasoline Cast iron sleeves, 35 cu. In. (570 cc) displacement, electronic ignition Full pressure lubrication with oil filter Engine mounted air cleaner and remote mounted Donaldson air intake Engine - remote mounted cyclonic air intake filtration
CONFIGURATION	3-wheel tricycle configuration, rear engine placement.
DRIVE	Direct drive hydrostatic variable displacement pump to two hydraulic drive motors on rear wheels and one hydraulic motor on front wheel. Series-Parallel traction drive to all 3 wheels. Hydraulic oil system cooler with engine driven air flow.
SPEED	Infinitely variable from 0 – 12 mph (20 kph) forward; 5 mph (8 kph) reverse
BRAKING	Dynamic braking through the hydrostatic transmission Hand operated, disc type park/emergency brake on rear wheel
CONSTRUCTION	Heavy gauge steel tubing, hydraulically formed, electrically welded.
TIRES/WHEELS	Purchasers choice of (3)22 x 11 x 10 knobbed sand tires, -or- (3) 23 – 10.5 x 12 turf tires
STEERING	Hydraulic power steering, 15” (38 cm) diameter automotive type, adjustable tilt steering wheel.
CONTROLS	Foot pedal for forward and rear operation of hydraulic system “Pro-Pedal” system connects engine throttle to hydraulic demand (Engine speed increases as hydraulic system demand increases) “Speed Boss” pre-set speed control system on hydrostatic transmission Hydraulic engage/disengage levers control rear mounted and center mounted implements
SEAT	Low back adjustable deluxe seat, 1 piece molded, ½ back support
ELECTRICAL	12 volt battery (280 cca); 12 volt electric starter, side mounted Ignition switch, operator presence switch in seat.
SOUND LEVEL	87dB(A) under normal operating conditions
DIMENSIONS (Inches/cm) (Length-Width-Height)	64 in (163 cm)-57 in (145 cm)-47 in (119 cm); Wheelbase: 41 in (104 cm) Ground Clearance 9” (23 cm) – under cultivator
WEIGHT	950 lbs (451 kg) 43-000
LIQUID CAPACITIES	Gasoline (unleaded): 5 gallons (19 liter) in high density nylon low-perm tank Hydraulic system oil: 5 gallons (19 liter) in high density polyethylene tank
SAFETY & CONFORMANCE	Complies with all applicable ANSI, OSHA, and European Machinery Directive standards
OPTIONS	42-315 Front Light Kit; 42-800 Certified ROPS; 15-622 Weather Canopy; 42-805 Fender Kit

IMPLEMENTS

Many efficient and effective implements for constructing and maintaining bunkers and surrounding areas

		SHIP WT.
Rear Mounted Implements		
13-298Q	Fan Rake for Sand Traps	36
13-319	Fan Rake Add On for 13-438 Rake Assembly	20
13-438Q	Sand Trap Rake Assembly	66
13-758	Max Flex Rake (2013 and Newer will replace 13-438)	66
13-684	Brush Attachment for all rakes except 42-130	20
13-740	Brush Attachment for 42-130	20
34-191	Box Grader	273
42-130Q	84" (213 cm) Mild Steel Tournament Rake	85
42-132Q	72" (189 cm) Mild Steel Tournament Rake	75
42-392Q	84" (213 cm) Multi Brush Rake	100
42-391Q	72" (189 cm) Multi Brush Rake	90
41-501	Typhoon Pumping System	480
43-010	Engine powered Leaf & Debris Blower	180
41-502	EarthWay [®] Spreader	50
Center Mounted Implements		
42-008	Sand Cultivator	20
42-223	Adjustable Disc Edger	30
42-750	Cart Path/Sidewalk Edger	30
42-340	Sand Cultivator w/Spring Tine Teeth	20
43-130	Weed Cultivator w/ Feet	25
Front Mounted Implements		
42-011	40" (102 cm) Front Mounted Plow (aluminum blade)	65
43-003	40" (102 cm) Hydraulic Plow	70
42-460	40" (102 cm) Adjustable Angle Plow	85
42-136	60" (155 cm) Front Mounted Manual Plow	75
42-490	60" (155 cm) Adjustable Angle manual Plow	100
GREEN STAR	ROLLER-BRUSH-SPIKER SYSTEM	
42-550Q	Green Star Total RBS System <i>Complete Roller, Brush and Spiker & mounting frame</i>	285
42-586Q	Green Star RBS Main Frame only <i>Mounting frame</i>	50
42-581	Green Star Roller Set (3) only (Requires 42-586Q Main Frame Assembly)	85
42-585	Green Star Brush Set (3) only (Requires 42-586Q Main Frame Assembly)	20
42-582	Green Star Spiker Set (3) only (Requires 42-586Q Main Frame Assembly)	130