

# Mete-R-Matic® XL ..... Tow-Type Topdresser



Sp

Model	M
Drive	V
Hopper Capacity	6
Hopper Size	T
Payload	6
Spreading Width	6
Topdressing Speed	U
Conveyor Belt	V
Metering Gate	T
Brush	9
Controls	E
Clutch	T
Wheels & Tires	T
Hitch	A
Empty Weight	2
Electrical Requirements	1

## The Ultimate in Topdressing Productivity

At 60.75 cubic feet, the hopper capacity of the Mete-R-Matic® XL is three times the size of the Mete-R-Matic III, for less reloading and increased efficiency on large turf areas.

- Patented ground-drive and Chevron® belt combines for the most consistent and uniform application in the industry.
- Patented Chevron belt can consistently handle all types of material such as compost, sand, peat, crumb rubber and calcine clays.
- Larger capacity hopper, that can easily be filled with a front-end loader, requires fewer trips to refill.



Ground-drive system means no tow vehicle calibration required; just hook up and go.



Easy on/off switch.



Patented continuous Chevron belt ensures uniform application.



Wide hopper capacity means less time reloading.

METE-R-MATIC is a registe

## Specifications

### Mete-R-Matic XL (#85460)

Wheels are driven by the ground; all six tires mechanically drive the conveyor and brush; no engine; no hydraulic system

10.75 ft<sup>3</sup> (1.72 m<sup>3</sup>; 2.25 yd<sup>3</sup>), galvanized panels

Top: 80" x 65.5" (2.03 m x 1.66 m)

Bottom: 60" x 46" (1.5 m x 1.17 m)

Depth: 18 ½" (0.47 m)

2,000 lb (2,721 kg)

60" (1.5 m)

Up to 8 MPH (12.8 km/h) loaded

Wide rubber composition with patented chevron belt 60" (1.5 m)

Maintor gate design is easily adjusted and provides uniform opening up to 2 ¼" (57 mm)

2" (228 mm) diameter, polypropylene bristle

Electrically operated clutch for conveyor and brush drive. Metering gate adjusted by hand.

The main clutch is a mechanical ratchet design actuated electrically from the operator's position on the tow vehicle

Two, 33" x 15.50" – 16.5" flotation tires

Adjustable height clevis 1" pin hitch

2,110 lb (957 kg) tow vehicle minimum

20 HP tractor (refer to Operator's Manual for additional requirements)

12 volt DC, negative ground (*electrical power provided by tow vehicle*)

Registered trademark of Turco Manufacturing, Inc.