

**ELITE SERIES** 

# UNLOCK THE FULL POTENTIAL OF THE WORKDAY.

The Hauler PRO Series has raised the bar for utility vehicles on the course with its reduced weight, remarkable range, and higher ground clearance on the Hauler PRO-X. The ELiTE lithium powertrain activated by Samsung SDI battery technology provides unmatched efficiency, zero emissions and reduced turf compaction, creating a vehicle that works just as hard as you do.



# ZERO Maintenance

ELITE LITHIUM BATTERY


1500LB / 1200LB

TOWING CAPACITY

1200LB / 900LB LOAD CAPACITY

12 CU FT

CARGO BED







**HAULER PRO ELITE** 

**HAULER PRO-X ELITE** 

### **ELITE LITHIUM POWERTRAIN**

- Zero Maintenance
- 5-Year Battery Warranty
- Lightweight Footprint
- Increased Efficiency
- Upgrade to 6.2 Triple Pack for Extended Range
- Standard Limited Slip Differential
- Standard Automatic Park Brake

## **OPTIONS & ACCESSORIES**

- 4-Wheel Mechanical Brakes
- Locking Glove Box
- Bed Dividers
- Floor Mount Attachment
- Windshield
- Canopy
- Electric Bed Lift
- 15 cu-ft Aluminum Bed with L-Track System
- Long-Handled Tool Holders
- Radio Holder
- Cargo Mesh Netting
- LED Headlights High/Low Beam
- LED Taillights/Brake Lights
- Ladder/Hoop Rack (Aluminum Bed Only)
- Rearview Mirror
- USB Port
- Unique Key Switch
- Side Body Color
- Weather Enclosure
- ROPS-Certified Cab
- Ball Cage
- Hubcaps
- Standard Rear Receiver Hitch
- Hour Meter
- Rapid On-Board Charger
- Drop-In Refresher (Plastic Bed Only)

# CUSHMAN.COM

# HAULER® PRO / ELITE SERIES

**HAULER PRO ELITE** 

HAULER PRO-X ELITE

BODY &	CHASSIS
--------	---------

FRAME	Welded Steel with E-Coat & DuraShield™ Powder Coat	
BODY & FINISH	Injection Molded TPO	
STANDARD COLOR	Forest Green	

### **DIMENSIONS**

119 in (302 cm)		
49 in (125 cm)		
70.5 in (179.1 cm)	77 in (196 cm)	
76.8 in (195 cm)	77.5 in (196.9 cm)	
35 in (88.9 cm)	38.0 in (96.56 cm)	
38.5 in (97.8 cm)		
4.3 in (11 cm)	5.5 in (14 cm)	
12 cu ft (0.34 m3)		
39 in (L) x 44 in (W) x 12 in (D) (99 cm x 111.8 cm x 30.5 cm)		
Roto-Molded Polyethylene		
	49 in ( 70.5 in (179.1 cm) 76.8 in (195 cm) 35 in (88.9 cm) 38.5 in ( 4.3 in (11 cm) 12 cu ft ( 39 in (L) x 44 i (99 cm x 111.8	49 in (125 cm)  70.5 in (179.1 cm)  77.5 in (196 cm)  76.8 in (195 cm)  77.5 in (196.9 cm)  35 in (88.9 cm)  38.5 in (97.8 cm)  4.3 in (11 cm)  5.5 in (14 cm)  12 cu ft (0.34 m3)  39 in (L) x 44 in (W) x 12 in (D)  (99 cm x 111.8 cm x 30.5 cm)

#### **POWER**

POWER SOURCE	56.7V Li-Ion Battery
MOTOR TYPE	AC Induction
HORSEPOWER (KW)	14.9 HP (11.1 kW)
ELECTRICAL SYSTEM	48V Primary, 12V Auxiliary
BATTERY (QTY/TYPE)	4.2 ELiTE - Twin Pack
BATTERY CHARGER	811 Watt World Charger
KEY OR PEDAL START	Pedal
DRIVE TRAIN	Motor Shaft Direct Drive
TRANSAXLE	Limited-Slip Differential with Helical Gears
SPEED CONTROLLER	350 Amp AC Controller
GEAR SELECTION	Dash Mounted Forward-Neutral-Reverse / Key Switch
REAR AXLE RATIO	16.99:1

### PERFORMANCE

SEATING CAPACITY	2-Person	
CURB WEIGHT	926 lb (420 kg)	971 lb (440 kg)
BED LOAD CAPACITY	800 lb (363 kg)	500 lb (227 kg)
VEHICLE LOAD CAPACITY	1200 lb (544 kg)	900 lb (408 kg)
SPEED	16.5 mph ± .05 mph (26.5 kph ± 0.8 kph)	
TOWING CAPACITY	1500 lb (680 kg) max	1200 lb (544 kg) max
OUTSIDE CLEARANCE CIRCLE	21.5 ft (6.6 m)	

# STEERING & SUSPENSION

STEERING	Self-Compensating Rack & Pinion	
SUSPENSION	Leaf Springs w/ Hydraulic Shock Absorbers	
SERVICE BRAKE	Dual Rear Wheel Mechanical, Self-Adjusting Drum	
PARKING BRAKE	Automatic Electro-Magnetic	
TIRES (FRONT & REAR)	18 x 8.5 - 8 (6 - Ply Tires)	20 x 8-10 (6 - Ply Tires)

